In the Claims

The status of claims in the case is as follows:

1	1.	[Currently amended] A method for control and
2	mana	gement of communication traffic, comprising the steps
3	of:	
4		expressing access rules as filters referencing system
_		-
5		kernel data;
6		for outbound processing, determining source application
7		indicia;
8	•	for inbound packet processing, executing a look-ahead
9		function to determine target application indicia; said
10		look-ahead function being executed within a protocol
11		stack including an IP layer, a transport layer, a
12		sockets layer, and an application layer and which, for
13		said inbound packet, said IP layer provides to said
14		transport layer said inbound packet, marked as non-
15		deliverable, and receives back from said transport
16		layer indicia, provided to said transport layer by said
17		sockets layer, identifying the application layer
18	•	application to which said packet would have been
19		delivered; and
20		responsive to said source or target application
21		indicia, executing filter processing: said filter
22		processing including constructing and evaluating
23		logical expressions of arbitrary length, and

Sep 09 2005 20:33 Attorney at	La
-------------------------------	----

24	selectively	using a	a set of]	Logical	operators,	
25	alternative	filter	selector	fields	and value	set.

- [Original] The method of claim 1, further comprising
- the steps of executing said determining and executing steps 2
- 3 within a kernel filtering function upon encountering a
- filter selector field referencing kernel data not included 4
- 5 in said packet.
- 1 [Original] The method of claim 1, said filter
- 2 processing including the steps of:
- determining a task or thread identifier; 3
- based on said task or thread identifier, determining a 4
- 5 process or job identifier; and
- based on said process or job identifier, determining 6
- 7 job or process attributes for filter processing.
- The method of claim 1, said filter 1 4. [Original]
- 2 processing including the steps of:
- 3 determining a user identifier; and
- based on said user identifier, determining user
- attributes for filter processing. 5
- 1 [Original] The method of claim 3, further comprising 5.
- 2 the step of determining from said task identifier a work
- 3 control block containing said process or job identifier.

3 of 40

p.6

1	6. [Canceled]
2	7. [Canceled]
1	8. [Original] The method of claim 1, further comprising
2	the steps of:
3	delivering to said filters infrastructure access rules
4	for defining security context.
1	9. [Original] The method of claim 8, said infrastructure
2	including logging, auditing, and filter rule load controls.
1	10. [Currently amended] A method for control and
2	management of aspects of communication traffic within
3	filtering, comprising the steps of:
4	receiving IP packet data into a TCP/IP protocol stack
5	executing within a system kernel;
6	for an inbound IP packet, executing a look-ahead
7	function within a protocol stack including an IP layer
8	a transport layer, a sockets layer, and an application
9	layer and which, for said IP inbound packet, said IP
10	layer provides to said transport layer said inbound IP
11	packet, marked as non-deliverable, and receives back
12	from said transport layer indicia, provided to said
13	transport layer by said sockets layer, identifying the

14

15

application layer application to which said packet

would have been delivered; and

p.7

22

fields, and value set.

16	executing filtering code within said system kernel with
17	respect to non-IP packet data accessed within said
18	system kernel outside of said TCP/IP protocol stack;
19	said filtering code constructing and evaluating logical
20 .	expressions of arbitrary length, and selectively using
21	a set of logical operators, alternative filter selector

- [Original] The method of claim 10, said non-IP packet 1 11.
- 2 data including context data regarding said IP packet.
- 1 12. [Original] The method of claim 10, said non-IP packet
- 2 data including data specific to a task generating said non-
- 3 IP packet data.
- 1 13. [Original] The method of claim 10, said non-IP packet
- 2 data including data specific to a task that will receive
- 3 said IP packet.
- [Original] The method of claim 11, said context data 1 14.
- including packet arrival interface indicia. 2
- 1 15. [Canceled]
- 2 16. [Canceled]
- 3 17. [Original]
- [Currently amended] A method for centralizing system-
- wide communication management and control within filter 5
- rules, comprising the steps of: 6
- 7 providing filter statements syntax for accepting
- parameters in the form of a selector, each selector

END920010019US1

5 of 40

,	apecitying herector freit, operator, and a sec or
10	<pre>values; [[and]]</pre>
11	for an inbound packet, executing a look-ahead function
12	within a protocol stack including an IP layer, a
13	transport layer, a sockets layer, and an application
14	layer and which, for said inbound packet, said IP layer
15	provides to said transport layer said inbound packet.
16	marked as non-deliverable, and receives back from said
17	transport layer indicia, provided to said transport
18	layer by said sockets layer, identifying the
19	application layer application to which said packet
20	would have been delivered by said sockets layer;
21	said selector referencing data that does not exist in
22	IP packets:
23	processing said filter statements, including
24	constructing and evaluating logical expressions of
	arbitrary length, and selectively using a set of
25	
26	logical operators, alternative filter selector fields,
27	and value set.
1	19. [Original] The method of claim 18, said parameters
2	selectively including userid, user profile, user class, user
3	group, user group authority, user special authority, job
4	name, process name, job group, job class, job priority,
5	other job or process attributes, and date & time.
1	20. [Original] The method of claim 18, said filters
2	statements being provided within a user interface to said

system.

3

ı	21.	[Original] The method of claim 18, further comprising
2	the	steps of:
_		
3		establishing a tunnel between two IP address limiting
4		traffic to applications bound to ports at each end of
5		said tunnel;
6		said filtering code accessing filtering attributes
7		further limiting traffic selectively to job indicia;
•		
8		and
9		operating said filtering code within a kernel filtering
10		function upon encountering a filter selector field
11		referencing kernel data not included in said traffic.
1	22.	[Currently amended] A method for traversing a portion
2	only	of a protocol stack to disallow selective IP packet
3	traf	fic, comprising the steps of:
	•	
4		receiving a packet in the kernel of the operating
5		system of a first node from an application, said kernel
6		including a filter processor; said filter processor for
7		constructing and evaluating logical expressions of
8		arbitrary length, said logical expressions selectively
9		including a set of logical operators, alternative
10		filter selector fields, and value set;
11	0.0	for inbound packet processing to a first node from a
12		second node, executing a look-ahead function in the
13		system kernel of said first node to determining

14	determine a target application; said system kernel
15	including a protocol stack including an IP layer, a
16	transport layer, a sockets layer, and an application
17	layer and which, for said inbound packet, said IP layer
18	provides to said transport layer said inbound packet,
19	marked as non-deliverable, and receives back from said
20	transport layer indicia identifying the application
21	layer application to which said packet would have been
22	<u>delivered:</u>
23	for both said inbound packet processing, and for
24	outbound packet processing from said first node to said
25	second node, executing within said kernel the steps of
26	processing said packet by determining a task ID;
27	responsive to said task ID, determining a
28	corresponding work control block;
29	determining a user ID, process or job identifier
30	from said work control block;
31	from the user ID, process or job identifier
32	selectively determining attributes for said user
33	process or job; and
34	passing said attributes to said filter processor
35	for managing and controlling communication
36	traffic.
1	23. [Currently amended] A method for expressing access
2	rules as filters, comprising the steps of:

S/N 09/919,185

		browing a firet pracement pluggi for accelering
4		parameters in the form of a selector, each selector
5		specifying selector field, operator, and a set of
6		values; and
7		said selector referencing data that does not exist in
8		IP packets for controlling access to an application;
9		for an inbound IP packet, executing a look-ahead
10		function within a protocol stack including an IP layer,
11		a transport layer, a sockets layer, and an application
12		layer and which, for said IP inbound packet, said IP
13 .		layer provides to said transport layer said inbound IP
14		packet, marked as non-deliverable, and receives back
15		from said transport layer indicia, provided to said
16		transport layer by said sockets layer, identifying the
17		application layer application to which said packet
18		would have been delivered; and
19		processing said filter statements by constructing and
20	•	evaluating logical expressions of arbitrary length.
21		said logical expressions selectively including a set of
22		logical operators, alternative filter selector fields.
23	•	and value set referencing said application layer
24		application.
1	24.	[Currently amended] A method for managing and
2	cont	rolling communication traffic by centralizing access
3	rule	s in filters executing within and referencing data
4 .	avai:	lable in system kernels, comprising the steps for
5	outb	ound packet processing from a first node to a second
6	node	of:

END920010019US1

9 of 40

,		receiving said packet in the kerner of the operating
8		system of said first node from an application or
9		process at said first node;
10		processing said packet by determining a task ID;
11		responsive to said task ID, determining a corresponding
12		work control block;
13		responsive to said work control block, determining a
14		process or job identifier;
		- X
15		responsive to said process or job identifier,
16		determining job or process attributes; and
17		executing said filters by constructing and evaluating
18		logical expressions of arbitrary length, said logical
19	٠.	expressions selectively including a set of logical
20		operators, alternative filter selector fields, and
21		value set.
1	25.	[Currently amended] The method of claim 24, further
2	comp:	rising the steps for inbound packet processing from said
3	seco	nd node to said first node of:
4		initially operating said kernel at said first node to
5		determine a target application for said packet at said
6		first node by executing a look-ahead function within a
7		protocol stack including an IP layer, a transport
8		layer, a sockets layer, and an application layer and
9		which, for said inbound packet, said IP layer provides
10		to said transport layer said inbound packet, marked as
	•	

S/N 09/919,185

11		non-deliverable, and receives back from said transport
12		layer indicia, provided to said transport layer by said
13		sockets layer, identifying the application layer
14		application to which said packet would have been
15		delivered:
	26.	[Canceled]
1	27.	[Canceled]
2	28.	[Canceled]
1	29.	[Currently amended] A method for managing and
2	cont	rolling communication traffic by centralizing the access
3	rule	s, comprising the steps for outbound packet processing
4	from	a first node to a second node of:
5		receiving said packet in the kernel of the operating
6		system of said first node from an application or
7		process at said first node, said kernel including a
8		filter processor for constructing and evaluating
9		logical expressions of arbitrary length, said logical
10		expressions selectively including a set of logical
11		operators, alternative filter selector fields, and
12		value set;
1.3		processing said packet by determining a task ID;
14		responsive to said task ID, determining a corresponding
15		work control block;
16		determining a user ID control block from said work
17	•	control block;
		·

11 of 40

18		from the user in control block determining attributes
19		for said user; and
20		passing said attributes to said filter processor for
21		managing and controlling communication traffic.
1	30.	[Currently amended] The method of claim 29, further
2	comp	rising the steps for inbound packet processing from said
3	_	nd node to said first node of:
4		initially operating said kernel at said first node to
5		determine a target application for said packet at said
6		first node by executing a look-ahead function within a
7		protocol stack including an IP layer, a transport
8	•	layer, a sockets layer, and an application layer and
9		which, for said inbound packet, said IP layer provides
10		to said transport layer said inbound packet, marked as
11	•	non-deliverable, and receives back from said transport
12		layer indicia, provided to said transport layer by said
13		sockets layer, identifying the application layer
14		application to which said packet would have been
15		delivered.
1	31.	[Canceled]
2	32.	[Canceled]
3	33.	[Canceled]
1	34.	[Currently amended] A method for control and
2		gement of communication traffic with respect to a system
3	node	, comprising the steps of:
4		receiving at said system node an inbound packet; and
	פרוזאים	20010019US1 12 of 40 S/N 09/919.185

5	executing within a protocol stack of the system kerner
6	of said system node a filtering function identifying
7	for said inbound packet a filter referencing non-packe
8	data, and constructing and evaluating logical
9	expressions of arbitrary length, said logical
10	expressions selectively including a set of logical
11	operators, alternative filter selector fields, and
12	value set; and
•	
13	responsive to said filter, executing a look-ahead
14	function for identifying a target application for said
15	inbound packet; said look-ahead function executed
16	within a protocol stack including an IP layer, a
17	transport layer, a sockets layer, and an application
18	layer and which, for said IP inbound packet, said IP
19	layer provides to said transport layer said inbound
20	packet, marked as non-deliverable, and receives back
21	from said transport layer indicia, provided to said
22	transport layer by said sockets layer, identifying the
23	application layer application to which said packet
24	would have been delivered:
1	35. [Original] The look-ahead function of the method of
2	claim 34 further comprising the steps of:
3	passing to a transport layer function identified by an
4	IP header a packet marked non-deliverable for
5	determining which user-level process or job is to
6	receive said packet;
7	receiving from said transport layer an application
8	layer task identifier for said user-level process or
	END920010019US1 13 of 40 S/N 09/919,185

10		passing said packet marked by said task identifier to
11		said transport layer for delivery to said application
12	•	layer task.
1	36.	[Currently amended] System for control and management
2	of c	ommunication traffic, comprising:
3		a system kernel including a filter function and stack
4		data;
5		said filter function including a filter selectively
6		referencing said stack data for expressing access
7		rules;
8		said filter function being responsive to receipt of an
9		outbound packet for determining a source application;
10		said filter function being responsive to receipt of an
11		inbound packet processing for executing a look-ahead
12		function within a protocol stack to determine a target
13	•	application; said protocol stack including an IP layer,
14		a transport layer, a sockets layer, and an application
15		layer and which, for said inbound packet, said IP layer
16		provides to said transport layer said inbound packet,
17		marked as non-deliverable, and receives back from said
18		transport layer indicia, provided to said transport
19		layer by said sockets layer, identifying the
20		application layer application to which said packet
21 .		would have been delivered; and

22	said filter function being responsive to said source of
23	target application for executing filter processing
24	including constructing and evaluating logical
25	expressions of arbitrary length, said logical
26	expressions selectively including a set of logical
27	operators, alternative filter selector fields, and
28	value set.
1	37. [Currently amended] A system for control and
2	management of aspects of communication traffic within
3	filtering, comprising:
4	a system kernel;
5	a protocol stack including an IP layer, a transport
6	layer, a sockets layer, and an application layer for
7	executing within said system kernel, responsive to an
8	inbound IP packet, a look-ahead function by which said
9	IP layer provides to said transport layer said inbound
10	IP packet, marked as non-deliverable, and receives bac
11	from said transport layer indicia, provided to said
12	transport layer by said sockets layer, identifying the
13	application layer application to which said packet
14	would have been delivered; and
15	filtering code within said system kernel operable with
16	respect to non-IP packet data accessed within said
17	system kernel outside of said protocol stack for
18	controlling and managing said aspects of communication
19	traffic: said filter code for constructing and
20	evaluating logical expressions of arbitrary length.
21	said logical expressions selectively including a set of
	·

END920010019US1

15 of 40

and value set.	
1 38. [Currently amended] A system for centralizing sy	stem-
wide communication management and control within filte	er
3 rules, comprising:	
4 filter statements having a syntax for accepting	
5 parameters in the form of a selector, each select	or
6 specifying selector field, operator, and a set of	<u>:</u>
7 values; [[and]]	
8 said selector referencing data that does not exis	st in
9 IP packets:	
10 a look-ahead function within a protocol stack inc	ludino
an IP layer, a transport layer, a sockets layer,	and ar
12 application layer which, for an inbound packet, s	aid IF
13 layer provides to said transport layer said inbou	nd
14 packet, marked as non-deliverable, and receives b	ack
15 <u>from said transport layer indicia, provided to sa</u>	<u>id</u>
16 transport layer by said sockets layer, for identi	fying
the application layer application to which said p	acket
18 would have been delivered; and	
a filter processor for constructing and evaluating	a
20 <u>filter statements including logical expressions o</u>	<u>f</u>
21 arbitrary length, said logical expressions select	ively
including a set of logical operators, alternative	
filter selector fields, and value set.	
1 39. [Currently amended] A system for traversing a pos	rtion
END920010019US1 16 of 40 S/N 09/91	9,185

2	only of a protocol stack to disallow selective IP packet
3	traffic, comprising:
4	a system kernel;
5	a filter processor executing within said system kerne
б	for constructing and evaluating logical expressions of
7	arbitrary length, said logical expressions selectively
8	including a set of logical operators, alternative
9	filter selector fields, and value set;
10	said filter processor responsive to an inbound packet
11	for executing a look-ahead function for determining a
12	target application; said look-ahead function operating
13	within a protocol stack including an IP layer, a
14	transport layer, a sockets layer, and an application
15	layer and which, for said IP inbound packet, said IP
16	layer provides to said transport layer said inbound I
17	packet, marked as non-deliverable, and receives back
18	from said transport layer indicia, provided to said
19	transport layer by said sockets layer, identifying the
20	application layer application to which said packet
21	would have been delivered;
22	said filter progessor responsive to both inhered and
23	said filter processor responsive to both inbound and
23	outbound packets for
24	processing said packet by determining a task ID;
25	responsive to said task ID, determining a
26	corresponding work control block;
	$oldsymbol{\cdot}$

27	determining a user ID, process or job identifier
28	from said work control block;
29	from the user ID, process or job identifier
30	selectively determining attributes for said user
31	process or job; and
. 32	passing said attributes to said filter processor
33	for managing and controlling communication
34	traffic.
•	
1	40. [Currently amended] A system for expressing access
2	rules as filters, comprising:
3	[[a]] filter statements for accepting parameters in the
4	form of a selector, each selector specifying selector
5	field, operator, and a set of values; [[and]]
•	
6	said selector referencing data that does not exist in
7	IP packets for controlling access to an application;
8	a look-ahead function executing within a protocol stack
9	including an IP layer, a transport layer, a sockets
10	layer, and an application layer and which, for an
11	inbound packet, said IP layer provides to said
12	transport layer said inbound packet, marked as non-
13	deliverable, and receives back from said transport
14	layer indicia, provided to said transport layer by said
15	sockets layer, identifying the application layer
16	application to which said packet would have been
17	delivered; and

18 of 40

18.	a filter processor for constructing and evaluating sale
19	filter statements as logical expressions of arbitrary
20	length, each said logical expression selectively
21	including said operator selected from a set of logical
22	operators, alternative filter selector fields, and
23	<u>value set</u> .
1	41. [Currently amended] A system for managing and
2	controlling communication traffic by centralizing access
3	rules in filters executing within and referencing data
4	available in system kernels, comprising:
5	a computer readable medium;
6	first code for receiving a packet in the kernel of the
7	operating system of a first node from an application of
8	process at said first node; said kernel responsive to
9	an inbound packet, for executing a look-ahead function
10	within a protocol stack including an IP layer, a
11	transport layer, a sockets layer, and an application
12	layer and which, for said inbound packet, said IP layer
13	provides to said transport layer said inbound IP
14	packet, marked as non-deliverable, and receives back
15	from said transport layer indicia, provided to said
16	transport layer by said sockets layer, identifying the
17	application layer application to which said packet
18	would have been delivered;
19	second code for processing said packet by determining a
20	task ID;
21	third code responsive to said task ID for determining a
	END920010019US1 19 of 40 S/N 09/919,185

22	•	corresponding work control block;
23		fourth code responsive to said work control block for
24		determining a process or job identifier; [[and]]
25		fifth code responsive to said process or job identifier
26		for determining job or process attributes;
27		sixth code for executing said filters by constructing
28		and evaluating logical expressions of arbitrary length.
29		said logical expressions selectively including a set of
30		logical operators, alternative filter selector fields,
31		and value set; and wherein
32		said first, second, third, fourth, fifth, and sixth
33		code is recorded on said computer readable medium.
1	42.	[Canceled]
2	43.	[Currently amended] A system for control and
3	mana	gement of communication traffic with respect to a system
4	node	, comprising:
5		a filtering function executing within a protocol stack
6		of the system kernel of said system node identifying
7		for an inbound packet a filter referencing non-packet
8		data; and
9		a look-ahead function responsive to said filter for
10		identifying a target application for said inbound
11		packet; said look-ahead function functioning within a
12	•	protocol stack including an IP layer, a transport
	END92	20010019US1 20 of 40 S/N 09/919,185

13		layer, a sockets layer, and an application layer and
14		which, for said inbound packet, said IP layer provides
15	4	to said transport layer said inbound packet, marked as
16		non-deliverable, and receives back from said transport
17		layer indicia, provided to said transport layer by said
18		sockets layer, identifying the application layer
19		application to which said packet would have been
20		delivered;; and
21		a filter processor for constructing and evaluating
22		logical expressions of arbitrary length, said logical
23		expressions selectively including a set of logical
24		operators, alternative filter selector fields, and
25		value set.
	44.	[Canceled]
1	45.	[Currently amended] A computer program product for
2	cont	rol and management of aspects of communication traffic
3	with	in filtering, said computer program product comprising:
4	-	a computer readable medium;
5		first species determined by species ID souther data
_	,	first program instructions to receive IP packet data
6		into a TCP/IP protocol stack executing within a system
7	•	kernel including, for processing an inbound IP packet,
8		a look-ahead function within a protocol stack including
9		an IP layer, a transport layer, a sockets layer, and an
10		application layer and which, for said IP inbound
11		packet, said IP layer provides to said transport layer
12	,	said inbound IP packet, marked as non-deliverable, and
13		receives back from said transport layer indicia,

T.4	provided to said transport layer by said sockets lay	<u>er.</u>
15	identifying the application layer application to whi	<u>ch</u>
16	said packet would have been delivered, [[and]]	
17	second program instructions to execute filtering cod	
18	within said system kernel with respect to non-IP pac	
19	data accessed within said system kernel outside of s	
20	TCP/IP protocol stack by constructing and evaluating	
21	logical expressions of arbitrary length, said logical	Ŀ
22	expressions selectively including a set of logical	
23	operators, alternative filter selector fields, and	
24	value set; and wherein	
25	said first and second program instructions are record	led
26	on said medium.	
-	46 (0	
1	46. [Currently amended] A [[a]] computer program product	:
2	for centralizing system-wide communication management and	
3	control within filter rules, said computer program product	;
4 .	comprising:	
5	a computer readable medium;	
6	first program instructions to execute filter statemen	ts
7	having a syntax for accepting parameters in the form	o£
8	a selector, each selector specifying selector field,	<u>a</u>
9	logical operator selected from a set of a plurality of	£
10	logical operators, and a set of values; and	
11	second program instructions to cause said selector to	
12	reference data that does not exist in IP packets, sai	
13	data including application layer indicia obtained for	
	THE THE PARTY OF THE TAKE THE CHAINED TO	
	END920010019US1 22 of 40 S/N 09/919,18	5

7.4	an incoming packet by a took-anead innection; said took-
15	ahead function executing within a protocol stack
16	including an IP layer, a transport layer, a sockets
17	layer, and an application layer and which, for said IP
18	inbound packet, said IP layer provides to said
19	transport layer said inbound IP packet, marked as non-
20	deliverable, and receives back from said transport
21	layer indicia, provided to said transport layer by said
22	sockets layer, identifying the application layer
23	application to which said packet would have been
24	delivered; and wherein
25	said first and second program instructions are recorded
26	on said medium.
1	47. [Currently amended] A [[a]] computer program product
2	for managing and controlling communication traffic by
3	centralizing access rules in filters executing within and
4	referencing data available in system kernels, said computer
5	program product comprising:
6	a computer readable medium;
7	first program instructions to receive said packet in
8	the kernel of the operating system of said first node
9	from a process at said first node;
10	second program instructions to process said packet by
11	determining a task ID;
12	third program instructions, responsive to said task ID,
13	to determine a corresponding work control block;
	END920010019US1 23 of 40 S/N 09/919.185

T-	routen program instructions, responsive to said work
15	control block, to determine a process or job
16	identifier; [[and]]
17	fifth program instructions, responsive to said process
18	or job identifier, to determine job or process
19	attributes; and
20	
	sixth program instructions to execute a filter
21	processor for constructing and evaluating logical
22	expressions of arbitrary length, said logical
.23	expressions selectively including a set of logical
24	operators, alternative filter selector fields, and
25	value set: and wherein
26	said first, second, third, fourth, and fifth fifth, and
27	
	sixth program instructions are recorded on said medium
1	48. [Previously presented] The computer program product of
2	claim 47, said computer program product further comprising
3	for inbound packet processing from said second node to said
4	first node:
5	sixth program instructions to initially operate said
6	kernel at said first node to determine a target
7	application for said packet at said first node by
8	executing a look-ahead function within a protocol stack
9	including an IP layer, a transport layer, a sockets
10	layer, and an application layer and which, for said IP
11	inbound packet, said IP layer provides to said
12	transport layer said inbound IP packet, marked as non-
13	deliverable, and receives back from said transport

T-1	tayer indicia, provided to baid cransport rayer by bur
15	sockets layer, identifying the application layer
16	application to which said packet would have been
17	<pre>delivered;; and wherein</pre>
18	said sixth program instructions are recorded on said
19	medium.
1	49. [Currently amended] A computer program product or
2	computer program element for control and management of
3	communication traffic, according to the steps comprising:
4	a computer readable medium:
. 5	first program instructions for expressing access rules
6	as filters referencing system kernel data;
7	second program instructions. for outbound processing,
8	for determining a source application;
9	third program instructions, for inbound packet
10	processing, for executing a look-ahead function to
11	determine a target application: said look-ahead
12	function operating within a protocol stack including an
13	IP layer, a transport layer, a sockets layer, and an
14	application layer and which. for said IP inbound
15	packet, said IP layer provides to said transport layer
16	said inbound IP packet, marked as non-deliverable, and
17	receives back from said transport layer indicia,
18	provided to said transport layer by said sockets layer.
19	identifying the application layer application to which
20	said packet would have been delivered; [[and]]

25 of 40

21

22	said source or target and target application, for
23	executing filter processing including constructing and
24	evaluating logical expressions of arbitrary length,
25	said logical expressions selectively including a set of
26	logical operators, alternative filter selector fields,
27 -	and value set;; and wherein
28	said first, second, third, and fourth program
29	instructions are recorded on said computer readable
30	medium.
1	50. [Currently amended] A computer program product or
2	computer program element for control and management of
3	aspects of communication traffic within filtering, according
4	to steps comprising:
5	a computer readable medium:
6	first program instructions for receiving IP packet data
7	into a TCP/IP protocol stack executing within a system
8	kernel;
9	second program instructions for executing filtering
10	code within said system kernel with respect to non-IP
11	packet data accessed within said system kernel outside
12	of said TCP/IP protocol stack: said filtering code
13	constructing and evaluating logical expressions of
14	arbitrary length, said logical expressions selectively
15	including a set of logical operators, alternative
16	filter selector fields, and value set; and wherein

fourth program instructions, selectively responsive to

- ·	THE PERSON DESCRIPTION OF A LECTION AND LECTION OF THE LECTION
18	on said computer readable medium.
1	51. [Currently amended] A computer program product or
	to an analysis of the state of
2	computer program element for centralizing system-wide
3	communication management and control within filter rules,
4	according to method steps comprising:
5	a computer readable medium:
6	first program instructions for providing filter
7	statements syntax for accepting parameters in the form
8	of a selector, each selector specifying selector field
9	a logical operator, and a set of values,
10 .	second program instructions for executing filtering by
11	constructing and evaluating logical expressions of
12	arbitrary length, said logical expressions selectively
13	including said logical operator selected from a set of
14	logical operators, at least one said selector field,
15	and at least one said value; [[and]]
16	said selector referencing data that does not exist in
17	IP packets including data obtained, for an inbound IP
18	packet, by executing a look-ahead function within a
19	protocol stack including an IP layer, a transport
20	layer, a sockets layer, and an application layer and
21	which, for said IP inbound packet, said IP layer
22	provides to said transport layer said inbound IP
23	packet, marked as non-deliverable, and receives back
24	from said transport layer indicia, provided to said
25 .	transport layer by said sockets layer, identifying the

26	application layer application to which said packet
27	would have been delivered;; and wherein
28	said first and second program instructions are recorded
29	on said computer readable medium.
1	52. [Currently amended] A computer program product or
2	computer program element for managing and controlling
3	communication traffic by centralizing access rules in
4	filters executing within, and referencing data available in,
5	system kernels, according to method steps comprising:
6	a computer readable medium:
7	first program instructions for receiving said packet in
8	the kernel of the operating system of said first node
9	from an application or process at said first node;
10	second program instructions for processing said packet
11	by determining a task ID;
12	third program instructions, responsive to said task ID,
13	for determining a corresponding work control block;
14	fourth program instructions, responsive to said work
15	control block, for determining a process or job
16	identifier;
17	fifth program instructions, responsive to said process
18	or job identifier, <u>for</u> determining job or process
19	attributes;

	DANCE PLOGRAM INDUITAGE FOR CACCACTING A LITTOR
21	processor for constructing and evaluating logical
22	expressions of arbitrary length, said logical
23	expressions selectively including a set of logical
24	operators, alternative filter selector fields, and
25	value set; and wherein
26	said first, second, third, fourth, fifth, and sixth
27	program instructions are recorded on said computer
28	readable medium.
1	53. [Currently amended] The computer program product or
2	element of claim 52, said method steps further comprising
3	for inbound packet processing from said second node to said
4	first node:
•	
5	seventh program instructions initially operating said
6	kernel at said first node to determine a target
7	application for said packet at said first node by
8	executing a look-ahead function within a protocol stack
9	including an IP layer, a transport layer, a sockets
10	layer, and an application layer and which, for said IP
11	inbound packet, said IP layer provides to said
12	transport layer said inbound IP packet, marked as non-
13	deliverable, and receives back from said transport
14	layer indicia, provided to said transport layer by said
15	sockets layer, identifying the application layer
16	application to which said packet would have been
17	delivered;; and wherein
18	said seventh program instructions are recorded on said
19	computer readable medium.
	END920010019US1 29 of 40 S/N 09/919,185